

Door Selector Guide



www.csfordoors.co.nz

Having been in doors since 1986, we understand how challenging it can be to choose the right door/s for your projects. This is especially true when you consider the variety of applications possible in contemporary building design. This guide has been designed to make the process of selecting the right doors, regardless of the application, easier for you. We hope you find it useful.

Please note that this list of doors and applications is a *guide* only. For further expert advice, please consult your Account Manager.

Range	Door style / type	Door Styles					Sizes			Thickness				Sound Qual			Usage Capability					
		Panelled	Glazed	Flush	Special	Pattern	Standard	Non-Standard	Over-Sized	35-38mm	38-40mm	55mm	65mm	Poor	Good	Up to STC 43 Rating	Cavity Sliders	Surface Sliders	Wardrobe Sliders	Pre-hung / Pivot*	Auto Door	Factory Door/Gate
CS DoorLeaves™ Std	NewYorker™ Up to 3200mm x 2700mm		✓				✓	✓	✓	✓				✓		✓	✓	✓	✓	✓	✓	
	AluLite™ Up to 3000mm x 4000mm			✓	✓	✓	✓	✓	✓	✓				✓	✓	✓				✓	✓	✓
	AluTeC™ Up to 3600mm x 2200mm			✓	✓		✓	✓	✓	✓	✓			✓		✓	✓	✓	✓	✓	✓	✓
	AluMaX™ Up to 6175mm x 6000mm	✓						✓	✓			✓		✓		✓	✓				✓	✓
	MirrorLite™ Up to 2400mm x 1200mm		✓	✓			✓	✓	✓		✓				✓		✓	✓	✓		✓	
CS Non Std	WhiteBoard™ Up to 2700mm x 1500mm			✓			✓	✓	✓		✓			✓		✓	✓	✓	✓	✓	✓	
	X-RayBarrier™ Up to 2700mm x 1800mm			✓			✓	✓	✓		✓				✓	✓	✓		✓	✓		
	FramelessGlass™ Up to 3000mm x 2000mm			✓		✓	✓	✓		10mm or 12mm toughened glass only				✓		✓	✓			✓		
Timber	1-light Stain Qual		✓				✓	✓		✓			✓			✓	✓	✓		✓		
	1-light Paint Qual		✓				✓	✓		✓			✓			✓	✓	✓		✓		
	Joinery Multi-light		✓			✓	✓	✓		✓			✓			✓	✓	✓		✓		
	Joinery Panel	✓				✓	✓	✓		✓			✓			✓	✓	✓		✓		
Generic Door Range	Flush H/C Door			✓			✓		✓				✓			✓	✓	✓				
	Flush S/C Door			✓			✓		✓					✓		✓	✓	✓				
	Non Std. Flush Door (55mm thick)		✓	✓		✓	✓	✓			✓		✓			✓	✓	✓		✓		
	V Grooved Doors					✓	✓			✓			✓			✓	✓	✓				
	4 Panel Doors	✓					✓		✓				✓			✓	✓	✓				
	Open Top Doors		✓				✓		✓				✓			✓	✓	✓				

© Cavity Sliders Limited 08.2011 - Door Selector:60005

*Pre-hung / Pivot Door sizes and applications will vary from nominated maximum door sizes on chart

AluTeC™ - Edge Profile Series

A top of the line aluminium framed and skinned door leaf with a 7mm vertical edge clashing and no visible screws or fastenings. This door will not rust, rot, or bow - even when made to oversize proportions.



- ▶ Door may be powder coated or primed ready for finishing
- ▶ Designed to suit sliding, hinged or even pivot applications.
- ▶ Suited to a maximum size of 3600 x 2200mm.
- ▶ Can be used in both interior and exterior situations.

NewYorker™

A pre-finished aluminium door frame that can be glazed using a wide range of materials, glass being the most common. Invisible fixings complement a robust frame that enables oversize door design whilst retaining classical dimensions and detail.



- ▶ Door frames may be powder coated or anodised.
- ▶ Designed to fit our sliding door hardware quickly and easily.
- ▶ Assembly materials used ensure doors will never rust, rot or bow.
- ▶ Styles: 100 or 70mm, Mid rails: 70 or 50mm.

AluMaX™

This door suits all extremes. You can expect the AluMaX to meet your design requirements whether they are based on looks, size or functionality. Manufactured entirely from aluminium, these doors suit interior or exterior conditions as wall sliders, gates or factory entries.



- ▶ Door sections may be powder coated or anodised.
- ▶ 65mm thickness ensures a robust feel and look is created.
- ▶ Assembly materials used ensure doors will never rust, rot or bow.

MirrorLitE™

Stability is assured with this high quality double sided mirror door that looks great in either residential or commercial applications. Full length mirror ensures the best viewing mirror door available. Supplied complete with built in edge pull and recessed side grips.



- ▶ Vertical edge clashings are natural anodised.
- ▶ Suited to a max. size of 2400 x 1200mm with no glass join.
- ▶ Door may be skinned with MDF on one side.

AluLitE™


The most versatile aluminium framed door in our range. Assembled with no visible screws or fastenings, this door incorporates many skin finishing options including Whiteboard / X-Ray / Patterned - all four edges are clashed neatly. Door cannot rust, rot or bow.



- ▶ Door frames may be skinned with a variety of materials.
- ▶ Most standard door hardware is easily factory fitted.
- ▶ Assembly materials used ensure doors will never rust, rot or bow.
- ▶ Limited glazing options are also available.

WhiteBoard™

A versatile pre-finished door panel that is suitable for cavity or surface sliding door applications. Both lightweight and durable, this door is used mostly in interior situations such as classrooms where an oversize room divider is required to double as a moveable wall and whiteboard.



- ▶ Pre-finished: manufactured in the factory to arrive on-site fully finished.
- ▶ Performs well acoustically with the correct accompanying door skins and insulation batts.

X-RayBarrier™

Designed for use in isotope areas or where diagnostic x-ray apparatus is used.

Many doors to x-ray areas are larger than standard and are heavy to operate due to their lead content. If the door is really big and heavy then we can fully automate the door, making use a breeze for all.



- ▶ Pre-finished in the factory to arrive on-site fully finished.
- ▶ Available with CaviLock handles and locks factory fitted.
- ▶ Strong, rigid construction ensures doors are stable under varying temperatures and changes of temperature.

CS CaviLock™

CaviLock, our hardware division, manufactures a range of high-quality security mortice locks and handles suitable for external or internal doors. If you are considering a lock and handle it may be worth thinking about our factory-fitting service, and have us fit the handle for you.



For more information,
phone 0800 SLIDERS
or email us on
info@csforddoors.co.nz

Quality products from
CS FOR DOORS®
www.csforddoors.co.nz